

# PROFESSIONAL ADVANCED REMOVER

Remover

## TECHNICAL DATA SHEET

### DESCRIPTION

PROFESSIONAL REMOVER is a stripper designed to remove PROFESSIONAL ADVANCED as well as PROFESSIONAL ADVANCED PRIMER. This stripper can be used for touching up or for a complete stripping of the hull in order to return to the PROFESSIONAL EPOXY PROTECT.

### APPLICATION

Apply with a brush in a thick coat of 2 mm.  
Allow to work for 2 to 3 hours so that the coating is completely softened.  
Remove residues with a spatula by rubbing in a circular motion.  
Repeat if necessary.  
Wipe off any residue with a cloth soaked in Xylene or light aromatic solvent.  
Can also be used for touch-ups on damaged surfaces.

### INSTRUCTIONS FOR USE

Mixing                      Stir well before use.

### APPLICATION RECOMMENDATIONS



Conditions

**Temperature** : 10-30°C. Ventilate well during application.  
Work in dry weather.



Application  
Methods

Roller or brush only

### PHYSICAL PROPERTIES



Theoretical  
spreading rate

**By roller/brush:** 3 m<sup>2</sup>/L per coat



Volatile Organic  
Compounds

VOC 645g/L



Color

Brown

# PROFESSIONAL ADVANCED REMOVER

## Remover

### GENERAL INFORMATION

---



Storage

Exposure to air and extremes of temperature should be avoided. For the full shelf life of this product to be realized ensure that between use the container is firmly closed and the temperature is between 5°C and 35°C. Keep out of direct sunlight. This product should be kept in securely closed containers.

Transportation

This product should be kept in securely closed containers during transport.

Shelf Life

2 years

Safety  
Precautions

Comply with all local safety, disposal and transportation regulations. Check the Material Safety Data Sheet (MSDS) and label of the individual products carefully before using the products. The MSDS's are available on our website or on request. The information given in this sheet is not exhaustive and can be modified when necessary.

**Disposal:** Do not discard tins or pour paint into water courses, use the facilities provided. It is best to allow paints to harden before disposal. Reminders of this product cannot be disposed of through the municipal waste route or dumped without permit. Disposal of remainders must be arranged for in consultation with the authorities.