

# PROFESSIONAL EPOXY THINNER

Epoxy thinner

## TECHNICAL DATA SHEET

### DESCRIPTION

Can be used to thin PROFESSIONAL EPOXY PROTECT.  
Also suitable for cleaning tools and equipment used with  
PROFESSIONAL FILLER LW or PROFESSIONAL FILLER.

### Surface conditions

When using for surface wipe down, turn the cloth frequently to avoid reapplying residues.



### RECOMMENDATIONS



Conditions

**Temperature:** 15-35°C  
Ensure adequate ventilation during use.



Volatile Organic  
Compounds

**VOC (As Supplied)** 857 g/L



Colour

Clear

### GENERAL INFORMATION



Storage

Exposure to air and extremes of temperature should be avoided.  
For the full shelf life of this product to be realized ensure that between use the container is firmly closed and the temperature is between 5°C and 35°C. Keep out of direct sunlight.  
This product should be kept in securely closed containers.

Transportation

This product should be kept in securely closed containers during transport.

Compatibility /  
Substrates

Compatible with all epoxy based primers and fillers. Read the datasheet for each individual product for specific thinning recommendations, which will depend upon how the product is to be used.

Shelf Life

2 years

Safety  
Precautions

Comply with all local safety, disposal and transportation regulations. Check the Material Safety Data Sheet (MSDS) and label of the individual products carefully before using the products. The MSDS's are available on our website or on request. The information given in this sheet is not exhaustive and can be modified when necessary.

**Disposal:** Do not discard tins or pour paint into water courses, use the facilities provided. It is best to allow paints to harden before disposal. Reminders of this product cannot be disposed of through the municipal waste route or dumped without permit. Disposal of reminders must be arranged for in consultation with the authorities.