

PROFESSIONAL THINNER

Thinner for antifoulings

TECHNICAL DATA SHEET

DESCRIPTION

Can be used to thin all Underwater Systems antifouling products and PROFESSIONAL PRIMER PROTECT.
 Can also be used to clean tools and equipment.

Surface conditions

When using for surface wipe down, turn the cloth frequently to avoid reapplying residues.



APPLICATION RECOMMENDATIONS



Conditions

Temperature: 15-35°C
 Ensure adequate ventilation during use.



Volatile
 Organic
 Compounds

VOC (As Supplied) 875 g/L



Colour

Clear

GENERAL INFORMATION



Storage

Exposure to air and extremes of temperature should be avoided.
 For the full shelf life of this product to be realized ensure that between use the container is firmly closed and the temperature is between 5°C and 35°C. Keep out of direct sunlight.
 This product should be kept in securely closed containers.

Transportation

This product should be kept in securely closed containers during transport.

Shelf Life

2 years

Safety Precautions

Comply with all local safety, disposal and transportation regulations.
 Check the Material Safety Data Sheet (MSDS) and label of the individual products carefully before using the products. The MSDS's are available on our website or on request. The information given in this sheet is not exhaustive and can be modified when necessary.

Disposal: Do not discard tins or pour paint into water courses, use the facilities provided. It is best to allow paints to harden before disposal. Reminders of this product cannot be disposed of through the municipal waste route or dumped without permit. Disposal of reminders must be arranged for in consultation with the authorities.